

**GSM status
Indicator LED**

**FIRMWARE
UPDATE
button**

**STATUS
operation
indicator LED**

POWER SUPPLY
12-30V DC or 12-24V AC

LINE OUTPUT
Simulated line
output

**FULL-FEATURED
RELAY OUTPUTS**
with NO/NC and
COM connections


**RS-232 serial port for
remote programming
of alarm panels**

TTL serial port

**6 CONTACT-CONTROLLED
inputs**

**ETHERNET
connector**

USB-C



**Nano SIM
(4FF)**

GSM ANTENNA
SMA antenna connector



ecoLINE PRO



ecoLINE PRO DIN rail



Discover the new generation of ecoLINE PRO transmitters with the ecoLINE PRO DIN rail!

With unchanged software and firmware features and an improved exterior, it will be available from 2025 with faster and simpler installation options. Simple setup and multi-level configurability.

Why choose the ecoLINE PRO DIN rail?

Internet connectivity: Ethernet and 4G support.

Built-in level shifter: No need to purchase an additional level shifter.

DIN rail compatibility: Simplifies and accelerates installation.

Practical front panel: The label with manufacturing information is placed on the front, ensuring it is always accessible.

Convenient Nano SIM usage: The SIM card can be easily inserted at the top of the device.

Wider power supply range: Supports 12–30 V DC and 12–24 V AC.

USB-C connector: Modern and fast connectivity option.

Mobile app support: Ensures more convenient control and access.

The **ecoLINE PRO DIN rail** is the perfect combination of cutting-edge technology and user-friendly design.

ecoLINE PRO-4G.IN4.R1

90 x 72 x 32 mm

Not available

Not available

Mini SIM (2FF)

Available

Not available

Not available

Available

Not available

USB A-B

Available

4 inputs and 1 output

Previously on the back of the device

No changes

Product types

Dimensions

24 V AC power supply

DIN rail mount

SIM card type

4G support

Ethernet support

TTL-level remote programming for alarm panels

RS-232 for remote programming of alarm panels

Built-in level shifter

Connector type

Mobile app

Number of inputs and outputs

Placement of manufacturing information label

Software and firmware

ecoLINE PRO DIN rail ETH.4G.IN6.R1

88,4 x 119 x 23,1 mm

Available

Available

Nano SIM (4FF)

Available

Available

Available

Available

Available

USB-C

Available

6 inputs and 1 output

Now placed on the front panel for better accessibility

No changes